




**DANE TECHNICZNE**

- współczynnik bezpieczeństwa: 4

**DOSTĘPNE DOKUMENTY**

- Specyfikacja techniczna produktu
- Atest 2.2 wg UNI EN10204



	art.	 Ø mm	 nr	WFL kg	m
<b>081200016</b>	8120 1,6X150	1,6	12	15	150
<b>081200022</b>	8120 2,2X75	2,2	14	25	75
<b>081200027</b>	8120 2,7X75	2,7	16	37	75
<b>081200034</b>	8120 3,4X60	3,4	18	75	60
<b>081200038</b>	8120 3,8X50	3,8	19	100	50
<b>081200044</b>	8120 4,4X40	4,4	20	125	40
<b>081200048</b>	8120 4,8X30	4,8	21	165	30
<b>081200055</b>	8120 5,5X25	5,5	22	185	25
<b>081200058</b>	8120 5,8X25	5,8	23	225	25
<b>081200065</b>	8120 6,5X25	6,5	24	265	25
<b>081200075</b>	8120 7,5X20	7,5	26	350	20
* <b>081200080</b>	8120 8,0X25	8,0	27	400	25
* <b>081200100</b>	8120 10,0X20	10,0	30	625	20
* <b>081200120</b>	8120 12,0X15	12,0	32	900	15