

# Wiha Bit holder with handle.

## Bit holder 1/4".



### 384 Bit holder with handle, magnetic, 1/4".

Blade: Chrome-vanadium steel, through hardened, nickel-plated.  
 Handle: Wiha SoftFinish® multi-component handle with roll-off protection.  
 Bit holder: Stainless steel with strong magnet.  
 Suitable for: For bits according to DIN 3126, ISO 1173 style C 6.3.

Order-No.	Ø	↔	↔	↕	↔
01475	1/4	125	225	36	10
01476	1/4	300	400	36	5



### 386 Bit holder with handle, flexible shaft, 1/4".

Blade: Plastic coated flexible metal.  
 Handle: Wiha SoftFinish® multi-component handle with roll-off protection.  
 Bit holder: With retaining ring.  
 Suitable for: For bits according to DIN 3126, ISO 1173 style C 6.3.  
 Application: For offset screws.

Order-No.	Ø	↔	↔	↕	↔
01479	1/4	150	268	36	10



### 387 Bit holder with handle, quick release holder, 1/4".

Handle: Wiha SoftFinish® multi-component handle with roll-off protection.  
 Bit holder: ClicFix quick release holder, magnetic.  
 Suitable for: For bits according to DIN 3126, ISO 1173 style C 6.3.  
 Application: Compact, handy style for working in confined spaces.  
 For applications where the bit must be held tight.

Order-No.	Ø	↔	↔	↕	↔
25874	1/4	35	146	30	10



### 281-02 Bit holder with handle, magnetic, 1/4".

Handle: Wiha SoftFinish® multi-component handle with roll-off protection.  
 Bit holder: Stainless steel with strong magnet.  
 Suitable for: For bits according to DIN 3126, ISO 1173 style C 6.3 and E 6.3.  
 Application: Compact screwdriver together with bits, 1/4".  
 Together with Wiha countersink bits, can be used as manual deburrer.

Order-No.	Ø	↔	↕	↔
32160	1/4	125	36	10

## Bit holder 1/4".



### 281 01 Bit holder with handle, magnetic, 1/4".

Handle: Ergonomic Wiha Stubby SoftFinish® handle, multi-component with roll-off protection.  
 Bit holder: Stainless steel with strong magnet.  
 Suitable for: For bits according to DIN 3126, ISO 1173 style C 6.3.  
 Application: For working in confined spaces.  
 Extra: Together with Wiha countersink bits, can be used as manual deburrer.

Order-No.	Ø	↔	↕	↔
29463	1/4	57	34	10



### 281-01ESD ESD bit holder with handle, retaining ring, 1/4". Dissipative handle, ESD-safe.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.  
 Surface resistance 10<sup>6</sup> - 10<sup>9</sup> ohms.  
 Universal use for all bits.  
 Standards: Handle: IEC 61340-5-1.  
 Output: For bits according to DIN 3126, ISO1173 style C 6.3.  
 Bit holder: Stainless steel with retaining ring.  
 Application: For working on electrostatically sensitive components, especially in tight places.

Order-No.	Ø	↔	↕	↔
32484	1/4	57	34	10



### 387ESD ESD bit holder with handle, quick release holder, 1/4". Dissipative handle, ESD-safe.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.  
 Surface resistance 10<sup>6</sup> - 10<sup>9</sup> ohms.  
 Standards: Handle: IEC 61340-5-1.  
 Output: For bits according to DIN 3126, ISO1173 style C 6.3, E 6.3 and double bits.  
 Input: DIN 3126, ISO 1173, style E 6.3.  
 Bit holder: Stainless steel with retaining ring.  
 Application: For working on electrostatically sensitive components.  
 With integrated CentroFix bit holder, suitable for all bits and bit drills with the style C 6.3, E 6.3 or double bits.  
 Extra: True single-handed operation, extremely high retention force of bits (up to 20 kg) and virtually no play between bit and holder thanks to special closing and holding mechanism.

Order-No.	Ø	↔	↔	↕	↔
32161	1/4	38	148	30	10

## Bit holder 1/4".

**388** Bit holder with handle, magnetic, 1/4".

Blade: Chrome-vanadium steel, through hardened, nickel-plated.  
 Handle: Wiha Classic T-handle.  
 Bit holder: Stainless steel with strong magnet.  
 Suitable for: For bits according to DIN 3126, ISO 1173 style C 6.3.  
 Application: For high torques.

Order-No.				
01481	1/4	150	80	10

**388DS** Bit holder with handle, magnetic, 1/4".

Blade: Chrome-vanadium steel, through hardened, nickel-plated.  
 Handle: Wiha ComfortGrip multi-component T-handle.  
 Bit holder: Stainless steel with strong magnet.  
 Suitable for: For bits according to DIN 3126, ISO 1173 style C 6.3.  
 Application: For high torques.  
 Extra: Two bit holders for 1/4" bits make this a universal tool.  
 Bit holder on the side for particularly high torque.

Order-No.				
26179	1/4	150	100	10

## Offset screwdriver.



57 Nm

**SB24628** High-performance offset screwdriver with a 105° angled head. Blister packed.

Suitable for: For bits according to DIN 3126, ISO 1173 style C 6.3 and E 6.3.  
 Material: Steel housing, chrome-plated.  
 Application: For use in almost any (battery-powered) screwdriver; ideal for drilling and fastening/unfastening in hard-to-reach places, corners and edges.  
 Extra: A hand-operated locking sleeve ensures an optimal hold of all 1/4" inserts such as bits, drill bits and countersink bits.  
 Stabilisation arm, adjustable in 48 positions;  
 torque transmission up to 57 Nm.  
 Compact, slim design.

Order-No.				
32310	1/4	1/4	165	1



14 Nm

**SB24629** Offset screwdriver with a 105° angled head, magnetic. Blister packed.

Suitable for: For bits according to DIN 3126, ISO 1173 style C 6.3 and E 6.3.  
 Material: Die cast housing, chrome-plated.  
 Application: For use in battery-powered and hand-held screwdrivers; ideal for drilling and fastening in hard-to-reach places, corners and edges.  
 Extra: Stabilisation arm, adjustable in 12 positions;  
 torque transmission up to 14 Nm.  
 Compact, slim design.

Order-No.				
32311	1/4	1/4	130	1