

Wiha CentroFix system.

Quick and professional.



Drilling, countersinking, driving screws and cutting threads is child's play with the Wiha CentroFix System. The innovative CentroFix quick-release holder forms the basis for a variety of hex-driven tools.

With CentroFix System, Wiha once again demonstrates that the user is central. The trend towards battery-powered drivers is continuing undiminished. Efficient models are greatly increasing the number of application areas and enabling more flexible working conditions. The Wiha CentroFix System also opens up these application areas to professional use.

With the CentroFix quick-release holder, Wiha closes the gap between the chuck of the battery-powered drivers and the quick-release holder for driver bits. The CentroFix holder allows rapid tool change, provides a secure fit and meets the more demanding requirements for concentricity and pull-off forces.



Flexible, easy and quick – drill, countersink and turn screws with the Wiha CentroFix System for wood ...

... or with the Wiha CentroFix System for metal.



Wiha CentroFix system.

Quick

- Saves time when changing tools

Secure

- Fixed connection between tool insert and holder

Zero-play

- For exact boreholes

Universal

- Fits all 1/4" hex drives

CentroFix - one for all.



7148C

CentroFix quick release holder, style E 6.3.

- Sleeve: Metal, coated.
- Suitable for: For bits according to DIN 3126, ISO 1173 style C 6.3 and E 6.3.
- Drive: DIN 3126, ISO 1173, style E 6.3.
- Packaging: Plastic box, reusable.
- Application: Whenever the bit needs a secure and zero-play hold. Optimised for the use of drill bits. Ideal for Torx bits.
- Extra: Due to the special holding mechanism, this bit holder holds all types of bits with 1/4" hex drive. The play between bit and holder is reduced to a minimum. Single-handed operation for fast bit exchange.

Order-No.	○	●	⊖	⊕
32477	1/4	1/4	60	10

Wiha drill bits.

Just keep on working.

Wood twist drill bit.



7804 Wood twist drill bit, style C 6.3.

Material: High grade chrome-molybdenum steel, ground.
Packaging: Blister packed.
Drive: With 1/4" hex shank according to DIN 3126 C 6.3.
Application: Especially suitable for boreholes in soft and hardwoods, as well as in veneered and coated laminated materials.
Extra: By means of careful rough-cutting, drilling of pocket holes is easy and does not tear the material.
 With centring tip for exact drilling.
 Particularly suitable for use in battery-powered drivers.

Order-No.	⊗	↔	↔	⊙	☰
27873	3.0	70	36	1/4	10
27876	4.0	75	43	1/4	10
27877	5.0	85	56	1/4	10
27879	6.0	95	66	1/4	10
27880	8.0	110	81	1/4	10
27881	10.0	110	81	1/4	10



79184 T19 Wood twist drill set, 19 pcs.

Pouch: High-quality nylon pouch, 13 x 2 x 10 cm.
Bits: 25 mm Standard and Torsion bits, wood twist drill bits, countersink bit.
Bit holder: CentroFix quick release holder, magnetic, style E 6.3.
Application: Compact range for drilling, countersinking and driving screws in wood.
Extra: Pouch with sturdy metal belt clip.

Order-No.	Series	☰			
28024	79184 T19	1			
⊗	7804	1x3.0	1x4.0	1x5.0	1x6.0
		1x8.0			
⊙	7806	1x12.4			
⊕	7011 ZOT	1xPH2			
⊕	7012 ZOT	1xPZ1	3xPZ2	1xPZ3	
⊗	7015 Z	1xT15	1xT20	1xT25	1xT30
⊙	7019 Z SIT	1xSIT 20	1xSIT 30		
	7148C	1xCentroFix quick release holder, style E 6.3			

7918 TL Nylon pouch, empty.

Order-No.	Series	☰
28028	7918 TL	1

Twist drill bit.



7805 Twist drill bit, style C 6.3.

Material: High-quality HSS steel, ground.
Packaging: Blister packed.
Drive: With 1/4" hex shank according to DIN 3126 C 6.3.
Application: Universal application in metal, plastic and wood.
Extra: Particularly suitable for use in battery-powered drivers.
 Special rivet-hole sizes 3.1, 4.1 and 5.1.

Order-No.	⊗	↔	↔	⊙	☰
27882	3.0	38	16	1/4	10
28055	3.1	38	16	1/4	10
27883	3.3	40	18	1/4	10
27884	4.0	43	22	1/4	10
28056	4.1	43	22	1/4	10
27885	4.2	43	22	1/4	10
27886	5.0	48	26	1/4	10
28057	5.1	48	26	1/4	10
27887	6.0	48	26	1/4	10
27888	6.8	48	30	1/4	10
27889	8.0	50	32	1/4	10
27890	8.5	51	34	1/4	10
27891	10.0	54	37	1/4	10



79185 T19 Twist drill set, 19 pcs.

Pouch: High-quality nylon pouch, 13 x 2 x 10 cm.
Bits: 25 mm Standard and Torsion bits, twist drill bits.
Bit holder: CentroFix quick release holder, magnetic, style E 6.3.
Application: Compact assortment for universal application when driving screws.
Extra: Pouch with sturdy metal belt clip.

Order-No.	Series	☰			
28025	79185 T19	1			
⊗	7805	1x3.0	1x4.0	1x4.2	1x5.0
		1x6.0	1x8.0		
⊕	7011 ZOT	2xPH1	3xPH2	1xPH3	
⊕	7012 ZOT	2xPZ2			
⊗	7015 Z	1xT15	1xT20	1xT25	1xT30
	7148C	1xCentroFix quick release holder, style E 6.3			

Combination drill bit and universal drill bit.



7807 Combination drill bit, style C 6.3.

Material: High-quality HSS steel, ground.
 Packaging: Blister packed.
 Drive: With 1/4" hex shank according to DIN 3126 C 6.3.
 Application: Drilling, cutting threads and burring. For assembly work, repair and rethreading.
 Can be used in metal and plastic.
 Extra: Three applications in a single work step. Particularly suitable for use in battery-powered drivers.

Order-No.	⊙	↔	⊙↓	↔
27897	M3	36	1/4	10
27898	M4	39	1/4	10
27899	M5	41	1/4	10
27900	M6	44	1/4	10
27901	M8	51	1/4	10
27963	M10	65	1/4	10

Countersink bit and bit holder.



7806 Countersink bit, style C 6.3.

Material: High-quality HSS steel, ground.
 Packaging: Blister packed.
 Drive: With 1/4" hex shank according to DIN 3126 C 6.3.
 Application: Universal application in metal, plastic and wood.
 Extra: Particularly suitable for use in battery-powered drivers. Guarantees outstanding removal of cuttings, no-rattle operation and smooth surface.

Order-No.	⊙	↔	⊙↓		∅ min.	↔
27892	6.3	35	1/4	M3	1.5	10
27893	8.3	35	1/4	M4	2.0	10
27894	10.4	35	1/4	M5	2.5	10
27895	12.4	35	1/4	M6	2.8	10
27896	16.5	35	1/4	M8	3.2	10
28058	20.5	35	1/4	M10	3.5	10



79187 B5 Combination drill bit set, 5 pcs.

Order-No.	Series	↔
28026	79187 B5	1
⊙	7807	M3x36 M4x39 M5x41 M6x44 M8x51



79186 B5 Countersink set, 5 pcs.

Order-No.	Series	↔
28027	79186 B5	1
⊙	7806	6.3x35 8.3x35 10.4x35 12.4x35 16.5x35



7848 Universal drill bit, style E 6.3.

Material: High-quality HSS steel, ground.
 Packaging: Blister packed.
 Drive: 1/4" hex universal drill in accordance with DIN 3126, style E 6.3.
 Application: For use in (battery-powered) screwdrivers; suitable for drilling holes in a multitude of materials (light masonry, light building materials, non-ferrous metal, metal, wood, plastics etc.) as well as light drilling on smooth and hard surfaces.
 Extra: Exact drilled holes via the special cutting edge. Especially long service life.

Order-No.	⊙	↔	↔	⊙↓	↔
32292	4	85	45	1/4	10
32293	5	96	50	1/4	10
32294	6	101	60	1/4	10
32295	7	101	60	1/4	10
32296	8	120	70	1/4	10
32297	10	120	70	1/4	10



281-02 Bit holder with handle, magnetic, 1/4".

Handle: Wiha SoftFinish® multi-component handle with roll-off protection.
 Bit holder: Stainless steel with strong magnet.
 Suitable for: For bits according to DIN 3126, ISO 1173 style C 6.3 and E 6.3.
 Application: Compact screwdriver together with bits, 1/4". Together with Wiha countersink bits, can be used as manual deburrer.

Order-No.	⊙	↔	↔	↔
32160	1/4	125	36	10