Wiha Classic electric.

The classic for electrical applications.

Safety Notice: When working with VDE tools, observe the national safety and accident prevention regulations!

For slotted and Phillips screws.

Classic electric slotted screwdriver.

Individually tested protective insulation 1,000 V AC, VDE and GS

Blade: Chrome-vanadium steel, through hardened, black-finish.

Insulation moulded directly onto blade.

Handle: Impact resistant Wiha Classic handle, resistant to chemicals and oils.

DIN ISO 2380. Manufactured acc. to IEC 60900:2012. Standards:

For all work on or around electrical components up to 1,000 V AC. Application:

	T		\sim		+			
Order-No.	1	 ■	\ominus	==	- ÷			
00782	1.6	40	0.4	115	19	10		
00783	2.3	60	0.5	135	19	10		
00784	2.5	75	0.4	150	19	10		
00785	2.8	75	0.6	150	19	10		
00786	3.0•	100	0.5	175	19	10		
06568	3.0	150	0.5	225	19	10		
00787	3.5	100	0.6	185	22	10		
00788	3.5	100	0.8	185	22	10		
00789	4.0	100	0.8	195	24	10		
06569	4.0	150	0.8	245	24	10		
00790	4.5	125	1.0	220	24	10		
00791	4.5•	175	1.0	270	24	10		
06570	5.0	100	1.0	195	24	10		
06571	5.0	150	1.0	245	24	10		
00792	5.5	125	1.0	230	28	10		
00793	5.5•	175	1.0	280	28	10		
06573	6.0	100	1.2	205	28	10		
00794	6.0	150	1.2	255	28	10		
00795	6.5	150	1.2	255	28	10		
00796	8.0	175	1.2	290	32	10		
00797	10.0	200	1.6	325	36	10		
Additional dimension, Non-DIN size,								





Classic electric Phillips screwdriver.

Individually tested protective insulation

1,000 V AC, VDE and GS tested.

Blade: Chrome-vanadium steel, through hardened, black-finish.

Insulation moulded directly onto blade.

Handle: Impact resistant Wiha Classic handle, resistant to chemicals and oils.

DIN ISO 8764. Manufactured acc. to IEC 60900:2012. Standards:

Application: For all work on or around electrical components up to 1,000 V AC.

Order-No.	(1)	 ■	==	— <u></u>	
00836	PH0	60	135	19	10
00837	PH1	80	175	24	10
00838	PH2	100	205	28	10
00839	PH3	150	265	32	10
00840	PH4	200	325	36	10

VDE slotted/ Phillips sets.



Classic electric slotted/Phillips screwdriver set, 6 pcs. 320 K6 Individually tested protective insulation 1,000 V AC, VDE and GS

> tested. Chrome-vanadium steel, through hardened, black-finish.

Blade: Insulation moulded directly onto blade.

Handle: Impact resistant Wiha Classic handle, resistant to chemicals and oils.

Manufactured acc. to IEC 60900:2012.

For all work on or around electrical components up to 1,000 V AC. Application:

Order-No. Series 00815 320 K6 1 320 2.8x75 4.0x100 5.5x125 6.5x150 321 PH1x80 PH2x100 **(1)**



320 P7 S0 Classic electric slotted/Phillips screwdriver set, 7 pcs.

Individually tested protective insulation 1,000 V AC, VDE and GS

tested.

Blade: Chrome-vanadium steel, through hardened, black-finish.

Insulation moulded directly onto blade.

Handle: Impact resistant Wiha Classic handle, resistant to chemicals and oils.

Standards: Manufactured acc. to IEC 60900:2012.

Application: For all work on or around electrical components up to 1,000 V AC.

Order-No. Series 07151 320 P7 SO 2.8x75 4.0x100 6.5x150 (1) 320 5.5x125 PH2x100 **⊕** 321 PH1x80 255-3L 3.0x60