Wiha flag and key handle.

The knack of applying just the right amount of pressure.



Screwdrivers with flag or key handles are used whenever replacing indexable inserts on milling heads.

Thanks to the large support area for thumb and index finger, it is possible to loosen or tighten any screw with comfort by applying just the right amount of pressure. These tools are also particularly suitable for high-torque adjustment work.





The small, 7-piece bench stand ensures a tidy working environment.

The flag and key handles have large support surfaces for thumb and index finger for ease of use and efficiency.



Wiha flag and key handle.

- Large support areas for thumb and index finger on the ergonomically shaped handles. The transmission of high torques is thus quite simple
- Cylindrical handle shaft for quick turning of screws
- Innovative torsion blade for T₅ to T₁₀ greatly reduces the risk of breakage. Thus, broken profiles in the screw head are largely avoided. If more torque than required is applied, the blade responds elastically (cf. picture)
- Thanks to thin blades, even covered screws in the screw axis can be turned

Wiha key handle.

For Allen screws and TORX® screws.



331 Hex driver with key handle.

Blade: Chrome-vanadium steel, through hardened, black-finish.

Handle: Wiha key handle.

Application: For high torque transfer with small screws, especially when replacing

indexable inserts on milling heads.

| Order-No. | • | ₩ | \Rightarrow | — (i) | |
|-----------|-----|----------|---------------|--------------|----|
| 00894 | 1.5 | 60 | 95 | 40 | 10 |
| 00895 | 2 | 60 | 95 | 40 | 10 |
| 00896 | 2.5 | 60 | 95 | 40 | 10 |
| 00897 | 3 | 60 | 95 | 40 | 10 |





TORX® driver with key handle.

Blade: Chrome-vanadium steel, through hardened, black-finish.

Handle: Wiha key handle.

Application: For high torque transfer with small screws, especially when replacing

indexable inserts on milling heads.

| Order-No. | • | ₩ | •1 | \Rightarrow | — • | |
|-----------|-----|----------|-----|---------------|------------|----|
| 04918 | T5 | 35 | 2.0 | 70 | 40 | 10 |
| 01350 | T6 | 35 | 2.0 | 70 | 40 | 10 |
| 01351 | T7 | 35 | 2.5 | 70 | 40 | 10 |
| 01352 | T8 | 40 | 2.5 | 75 | 40 | 10 |
| 01353 | T9 | 40 | 3.0 | 75 | 40 | 10 |
| 01354 | T10 | 40 | 3.0 | 75 | 40 | 10 |
| 01355 | T15 | 45 | 3.5 | 80 | 40 | 10 |
| 01356 | T20 | 45 | 4.0 | 80 | 40 | 10 |





TORX® screwdriver set with key handle.

In small bench stand, 7 pcs.

Blade: Chrome-vanadium steel, through hardened, black-finish.

Handle: Wiha key handle.

Application: For high torque transfer with small screws, especially when replacing

indexable inserts on milling heads.

Extra: Small, robust metal workbench holder to stand on workbench.

Tip diagrams printed to scale.

| Order-No. | Series | | | | |
|-----------|--------|-------|--------|--------|--------|
| 25624 | 365 VB | | | | 1 |
| • | 365 | T6x35 | T7x35 | T8x40 | |
| | | T9x40 | T10x40 | T15x45 | T20x45 |

For TORX PLUS® screws.



365IP TORX PLUS® driver with key handle.

Blade: Chrome-vanadium steel, through hardened, black-finish.

Handle: Wiha key handle.

Application: For high torque transfer with small screws, especially when replacing

indexable inserts on milling heads.

Extra: The stronger profile of the TORX PLUS® tip allows up to 25% extra

torque than the TORX® profile.

Attention: TORX PLUS® keys cannot be used with TORX® screws.

| Order-No. | • | ₩ | •1 | $\qquad \qquad \Longrightarrow$ | — (i) | |
|-----------|--------------|----------|-----|---------------------------------|--------------|----|
| 26181 | 5IP | 35 | 2.0 | 70 | 40 | 10 |
| 26182 | 6IP | 35 | 2.0 | 70 | 40 | 10 |
| 26183 | 7 I P | 35 | 2.5 | 70 | 40 | 10 |
| 26184 | 8IP | 40 | 2.5 | 75 | 40 | 10 |
| 26185 | 9IP | 40 | 3.0 | 75 | 40 | 10 |
| 26186 | 10IP | 40 | 3.0 | 75 | 40 | 10 |
| 26187 | 15IP | 45 | 3.5 | 80 | 40 | 10 |
| 26188 | 20IP | 45 | 4.0 | 80 | 40 | 10 |





65IP VB TORX PLUS® driver set with key handle.

In small bench stand, 7 pcs.

Blade: Chrome-vanadium steel, through hardened, black-finish.

Handle: Wiha key handle.


 $\label{eq:Application: For high torque transfer with small screws, especially when replacing} Application: \\$

indexable inserts on milling heads.

Extra: Small, robust metal workbench holder to stand on workbench.

Tip diagrams printed to scale.

| Order-No. | Series | | | | |
|-----------|----------|-----------------|------------------|------------------|------------------|
| 26261 | 365IP VB | | | | 1 |
| • | 365IP | 6 I Px35 | 7IPx35 | 8IPx40 | |
| | | 9 I Px40 | 10 I Px40 | 15 I Px45 | 20 I Px45 |



Wiha flag handle and offset screwdrivers.

For TORX® and TORX PLUS® screws.

370 TORX® driver with flag handle.

Blade: Chrome-vanadium steel, through hardened, black-finish.

Handle: Wiha flag handle

Application: For high torque transfer with small screws, especially when replacing

indexable inserts on milling heads.

| Order-No. | | ₩ | •1 | \Rightarrow | — ∅‡ | |
|-----------|-----|----|-----|---------------|-------------|----|
| 03724 | T5 | 35 | 2.0 | 62 | 15 | 10 |
| 03725 | T6 | 35 | 2.0 | 62 | 15 | 10 |
| 03726 | T7 | 35 | 2.5 | 67 | 19 | 10 |
| 03727 | T8 | 40 | 2.5 | 72 | 19 | 10 |
| 03728 | T9 | 40 | 3.0 | 74 | 24 | 10 |
| 03729 | T10 | 40 | 3.0 | 74 | 24 | 10 |
| 03730 | T15 | 45 | 3.5 | 80 | 28 | 10 |
| 03731 | T20 | 45 | 4.0 | 80 | 28 | 10 |



TORX® driver set with flag handle. In small bench stand, 7 pcs.

| Order-No. | Series | | | | |
|-----------|--------|-------|--------|--------|--------|
| 25625 | 370 VB | | | | 1 |
| • | 370 | T6x35 | T7x35 | T8x40 | |
| | | T9x40 | T10x40 | T15x45 | T20x45 |



70IP TORX PLUS® driver with flag handle.

Blade: Chrome-vanadium steel, through hardened, black-finish.

Handle: Wiha flag handle

 $\label{eq:policy} \textit{Application:} \qquad \textit{For high torque transfer with small screws, especially when replacing}$

indexable inserts on milling heads.

Extra: The stronger profile of the TORX PLUS® tip allows up to 25% extra

torque than the TORX $\!\!^{\scriptscriptstyle{(\!0\!)}}$ profile.

Attention: TORX PLUS® keys cannot be used with TORX® screws.

| Order-No. | • | ₩ | •1 | | — 0∶ | |
|-----------|--------------|----------|-----|---------|-------------|----|
| 27614 | 5IP | 35 | 2.0 | 67 | 15 | 10 |
| 27615 | 6IP | 35 | 2.0 | 67 | 15 | 10 |
| 27616 | 7 I P | 35 | 2.5 | 67 | 19 | 10 |
| 27617 | 8IP | 40 | 2.5 | 72 | 19 | 10 |
| 27618 | 9IP | 40 | 3.0 | 74 | 24 | 10 |
| 27619 | 10IP | 40 | 3.0 | 74 | 24 | 10 |
| 27620 | 15IP | 45 | 3.5 | 80 | 28 | 10 |
| 27621 | 20IP | 45 | 4.0 | 80 | 28 | 10 |

For slotted, Phillips and Pozidriv screws.



207 Slotted offset screwdriver with handle.

Blade: Chrome-vanadium steel, through hardened, chrome-plated.

Standards: DIN 5200.

Application: For working in confined spaces.

| Order-No. | Φ | \ominus ; | \rightleftharpoons | ļr—, | •1 | | | |
|--------------------------------|-------------------------------------|-------------|----------------------|------|------|----|--|--|
| 00373 | 3.5 | 0.6 | 90 | 8.5 | 3.5 | 10 | | |
| 00374 | 4.0 | 0.8 | 100 | 9.0 | 4.0 | 10 | | |
| 00375 | 5.5 | 1.0 | 125 | 10.5 | 5.5 | 10 | | |
| 00376 | 6.5• | 1.2 | 125 | 13.5 | 6.5 | 10 | | |
| 00377 | 8.0 | 1.2 | 150 | 17.0 | 8.0 | 10 | | |
| 00378 | 10.0 | 1.6 | 175 | 24.0 | 9.0 | 10 | | |
| 00379 | 12.0 | 2.0 | 200 | 27.0 | 10.0 | 5 | | |
| Additional | Additional dimension. Non-DIN size. | | | | | | | |

NEW

Slotted offset screwdriver with handle.

Blister packed.

| Order-No. | Φ | \ominus ; | \rightleftharpoons | ţr — , | •1 | |
|-----------|--------|-------------|----------------------|---------------|-----|---|
| 04451 | 5.5 | 1.0 | 125 | 10.5 | 5.5 | 1 |



Phillips offset screwdriver with handle.

Blade: Chrome-vanadium steel, through hardened, chrome-plated.

Standards: DIN 5208.

00434

PZ3

PZ4

Application: For working in confined spaces.

| Order-No. | ⊕ | ⊕ | \rightleftharpoons | ţ r— , | •1 | |
|-----------|----------|----------|----------------------|---------------|------|----|
| 00144 | PH1 | PH2 | 125 | 14.5 | 5.5 | 10 |
| 00145 | PH2 | PH3 | 150 | 21.0 | 8.0 | 10 |
| 00146 | PH3 | PH4 | 200 | 25.0 | 10.0 | 10 |

NEW SB 161 Phillips offset screwdriver with handle. Blister packed.

| Order-No. | ⊕ | ⊕ | \rightleftharpoons | ţ r— , | •1 | |
|-----------|----------|----------|----------------------|---------------|-----|---|
| 04454 | PH1 | PH2 | 125 | 14.5 | 5.5 | 1 |
| 04455 | PH2 | PH3 | 150 | 21 | 8 | 1 |



25.0

200

10.0

10