

Wiha SoftFinish® electric.

The safe and comfortable insulated VDE screwdriver.



The right tool at a glance, thanks to the printed screw symbol on the handle end.



For slotted screws.



320N

SoftFinish® electric slotted screwdriver.

Individually tested protective insulation 1,000 V AC, VDE and GS tested.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, black-finish.

Insulation moulded directly onto blade.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Standards: DIN ISO 2380.

Manufactured acc. to IEC 60900:2012.

Application: For all work on or around electrical components up to 1,000 V AC.

Order-No.	①	↔	⊕	↔	↔	↔
00819	2.0	60	0.4	164	23	10
00820	2.5	75	0.4	179	23	10
00821	3.0	100	0.5	204	23	10
00822	3.5	100	0.6	204	23	10
00823	4.0	100	0.8	211	30	10
00824	4.5•	125	1.0	236	30	10
00825	4.5•	175	1.0	286	30	5
31863	4.5•	200	1.0	311	30	10
00826	5.5	125	1.0	243	36	10
00827	5.5•	175	1.0	293	36	5
00828	6.0•	150	1.2	268	36	10
00829	6.5	150	1.2	268	36	10
00830	8.0	175	1.2	299	41	10
00831	8.0	175	1.6	299	41	10
00832	10.0	200	1.6	324	41	10

• Additional dimension, Non-DIN size.



Wiha SoftFinish® electric.

- Safety when working with live equipment up to 1,000 V AC and 1,500 V DC
- Each screwdriver is individually tested in a water bath at 10,000 volts according to IEC 60900:2012
- Awarded the GS symbol for tested safety
- Multi-component SoftFinish® handle provides maximum user comfort

Applications on live equipment are subject to very special requirements. The focus is on absolute user safety and Wiha demonstrates this with a wealth of details.

The high quality blade insulation is moulded directly onto the blade and therefore guarantees safety when working on live equipment up to 1,500 V DC / 1,000 V AC. To maintain this safety, each screwdriver of the SoftFinish® electric series is individually tested in a water bath at 10,000 Volts according to IEC 60900:2012.

The roll-off protection and the special handle geometry offer optimum handling and electrical safety, even in critical applications.

Wiha SoftFinish® electric.

The safe and comfortable insulated VDE screwdriver.

For Phillips, Pozidriv and TORX® screws.



1000 V
IEC 60900:2012

321N SoftFinish® electric Phillips screwdriver.

Individually tested protective insulation
1,000 V AC, VDE and GS tested.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, black-finish.

Insulation moulded directly onto blade.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Standards: DIN ISO 8764. Manufactured acc. to IEC 60900:2012.

Application: For all work on or around electrical components up to 1,000 V AC.

Order-No.	PH0	PH1	PH2	PH3	PH4
00846	60	164	23	10	
00847	80	191	30	10	
00848	100	218	36	10	
00849	150	268	41	10	
00850	200	318	41	5	



1000 V
IEC 60900:2012

324 SoftFinish® electric Pozidriv screwdriver.

Individually tested protective insulation
1,000 V AC, VDE and GS tested.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, black-finish.

Insulation moulded directly onto blade.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Standards: DIN ISO 8764. Manufactured acc. to IEC 60900:2012.

Application: For all work on or around electrical components up to 1,000 V AC.

Order-No.	PZ0	PZ1	PZ2	PZ3
00877	60	164	23	10
00878	80	191	30	10
00879	100	218	36	10
00880	150	324	41	5



1000 V
IEC 60900:2012

325 SoftFinish® electric TORX® screwdriver.

Individually tested protective insulation
1,000 V AC, VDE and GS tested.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, black-finish.

Insulation moulded directly onto blade.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Standards: Manufactured acc. to IEC 60900:2012.

Application: For all work on or around electrical components up to 1,000 V AC.

Extra: Sizes T10 to T40 are in the 3251 series with the slimFix screwdrivers.

Order-No.	T5	T6	T7	T8	T9
03760	60	164	23	10	
03761	60	164	23	10	
03762	60	164	23	10	
00881	60	164	23	10	
00882	60	164	23	10	

For allen screws and internal square-drive screws.



1000 V
IEC 60900:2012

322 SoftFinish® electric hex nut driver.

Individually tested protective insulation
1,000 V AC, VDE and GS tested.

Blade: Chrome-vanadium steel, through hardened, black-finish. Insulation moulded directly onto blade.

Deep drawn socket.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Standards: DIN 3125. Manufactured acc. to IEC 60900:2012.

Application: For external hex screws and hex nuts.

Order-No.	4	5	5.5	6	7	8	9	10	11	12	13	14	15	16	17
00853	125	236	30	10.2	10										
00855	125	236	30	11.2	10										
00856	125	236	30	11.2	10										
00857	125	236	30	12.2	10										
00858	125	243	36	14.5	10										
00859	125	243	36	15.2	10										
00860	125	243	36	16.0	10										
00861	125	243	36	17.2	10										
00862	125	243	41	19.2	5										
00863	125	243	41	20.2	5										
00864	125	243	41	22.2	5										
00865	125	243	41	23.2	5										
00866	125	243	41	25.2	5										
00867	125	243	41	25.2	5										
00868	125	243	41	27.2	5										



1000 V
IEC 60900:2012

323N SoftFinish® electric hex screwdriver.

Individually tested protective insulation
1,000 V AC, VDE and GS tested.

Blade: Chrome-vanadium steel, through hardened, black-finish. Insulation moulded directly onto blade.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Standards: Manufactured acc. to IEC 60900:2012.

Application: For allen screws.

Order-No.	2.5	3.0	4.0	5.0	6.0	8.0
30361	75	179	23	10		
30362	75	179	23	10		
30363	75	186	30	10		
30364	75	186	30	10		
30365	100	218	36	10		
30366	100	218	36	10		



1000 V
IEC 60900:2012

358N SoftFinish® electric square (Robertson) screwdriver.

Individually tested protective insulation
1,000 V AC, VDE and GS tested.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, black-finish. Insulation moulded directly onto blade.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Standards: Manufactured acc. to IEC 60900:2012.

Application: For fastening and unfastening internal square-drive (Robertson) screws.

Order-No.	Robertson 1	Robertson 2	2.3	2.8	100	211	30	36	10
32396									
32397									

**Safety Notice:**

When working with Wiha tools, observe the national safety and accident prevention regulations!

**Slotted/ Phillips and slotted/ Pozidriv sets.**

320N K6 SoftFinish® electric slotted/ Phillips screwdriver set, 6 pcs.
Individually tested protective insulation
1,000 V AC, VDE and GS tested.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, black-finish. Insulation moulded directly onto blade.
Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.
Standards: Manufactured acc. to IEC 60900:2012.
Application: For all work on or around electrical components up to 1,000 V AC.

Order-No.	Series				
00833	320N K6				1
①	320N	3,0x100	4,0x100	5,5x125	6,5x150
⊕	321N	PH1x80	PH2x100		

Slotted/Phillips- and nut driver set.

with
voltage tester

320N K7 SoftFinish® electric slotted/ Phillips screwdriver set, 7 pcs.
Individually tested protective insulation
1,000 V AC, VDE and GS tested.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, black-finish. Insulation moulded directly onto blade.
Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.
Standards: Manufactured acc. to IEC 60900:2012.
Application: For all work on or around electrical components up to 1,000 V AC.

Order-No.	Series				
00834	320N K7				1
①	320N	2,5x75	4,0x100	5,5x125	6,5x150
⊕	321N	PH1x80	PH2x100		
①	255-11L	3,0x60			



320N ZK6 SO SoftFinish® electric slotted/ Pozidriv screwdriver set, 6 pcs.
Individually tested protective insulation 1,000 V AC, VDE and GS tested.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, black-finish. Insulation moulded directly onto blade.
Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.
Standards: Manufactured acc. to IEC 60900:2012.
Application: For all work on or around electrical components up to 1,000 V AC.

Order-No.	Series				
25477	320N ZK6 SO				1
①	320N	2,5x75	3,5x100	4,5x125	5,5x125
⊕	324	PZ1x80	PZ2x100		



322 K5 SoftFinish® electric hex nut driver set, 5 pcs.
Individually tested protective insulation
1,000 V AC, VDE and GS tested.

Blade: Chrome-vanadium steel, through hardened, black-finish. Insulation moulded directly onto blade. Deep drawn socket.
Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.
Standards: Manufactured acc. to IEC 60900:2012.
Application: For all work on or around electrical components up to 1,000 V AC.

Order-No.	Series				
29466	322 K5				1
⊙	322	5,5x125	7x125	8x125	10x125
		13x125			

Wiha SoftFinish® electric Xeno.

For terminal screws.



The SoftFinish® electric Xeno screwdriver is a special VDE screwdriver used to turn terminal screws. Terminal screws are typically used in switch-cabinet systems and fuse boxes, terminal blocks and relays.

They have a special combination profile and are available as slotted/Phillips or slotted/Pozidriv models.



The Wiha SoftFinish® electric Xeno is ideally suited for work on switch cabinet systems, fuse boxes, terminal strips and relays.



Wiha SoftFinish® electric Xeno.

- The special slotted/ Phillips or slotted/ Pozidriv profile of the Xeno is optimally suited for terminal screws
- The combination profile reduces slipping and ensures greater torque transfer

**Safety Notice:**

When working with VDE tools, observe the national safety and accident prevention regulations!

**For terminal screws (slotted/ Phillips).****327 SoftFinish® electric Xeno.**

For terminal screws (slotted/ Phillips).

Individually tested protective insulation 1,000 V AC, VDE and GS tested.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, black-finish.

Insulation moulded directly onto blade.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Standards: Manufactured acc. to IEC 60900:2012.

Application: For all work on or around electrical components up to 1,000 V AC. No slipping and better torque transfer with terminal screws e.g. in switch-cabinets, fuse boxes and terminal blocks.

Order-No.	⊕	80	191	30	10
30716	SL/PH1				
30715	SL/PH2				

For terminal screws (slotted/ Pozidriv).**328 SoftFinish® electric Xeno.**

For terminal screws (slotted/ Pozidriv).

Individually tested protective insulation 1,000 V AC, VDE and GS tested.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, black-finish.

Insulation moulded directly onto blade.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Standards: Manufactured acc. to IEC 60900:2012.

Application: For all work on or around electrical components up to 1,000 V AC. No slipping and better torque transfer with terminal screws e.g. in switch-cabinets, fuse boxes and terminal blocks.

Order-No.	⊕	80	191	30	10
30700	SL/PZ1				
30701	SL/PZ2				

**SB 327 S2 SoftFinish® electric Xeno screwdriver set, 2 pcs.**

For terminal screws (slotted/ Phillips).

Individually tested protective insulation 1,000 V AC, VDE and GS tested.

Blister packed.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, black-finish.

Insulation moulded directly onto blade.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Standards: Manufactured acc. to IEC 60900:2012.

Application: For all work on or around electrical components up to 1,000 V AC.

Order-No.	Series	
32281	SB 327 S2	1
⊕	327	SL/PH1x80 SL/PH2x100

**SB 328 S2 SoftFinish® electric Xeno screwdriver set, 2 pcs.**

For terminal screws (slotted/ Pozidriv).

Individually tested protective insulation 1,000 V AC, VDE and GS tested.

Blister packed.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, black-finish.

Protective insulation moulded directly onto the blade.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Standards: Manufactured acc. to IEC 60900:2012.

Application: For all work on or around electrical components up to 1,000 V AC.

Order-No.	Series	
32282	SB 328 S2	1
⊕	328	SL/PZ1x80 SL/PZ2x100