

# Wiha Torque ESD torque range.



TorqueVario®-S ESD with scale.

with scale



2882

TorqueVario®-S ESD torque screwdriver.

Torque value can be set via window scale.

Automatic release.

Handle:

Torque infinitely adjustable with Torque-Setter setting tool (also supplied).

Ergonomic multi-component handle, made of ESD-safe dissipative material.

Handle sizes proportioned to optimise torque setting.

Audible and perceptible click when the pre-set torque has been attained.

Surface resistance  $10^6 - 10^9$  ohms.

Compatible with all blades of the 2889 series.

Standards:

IEC 61340-5-1.

EN ISO 6798, BS EN 26789, ASME B107.14M.

Accuracy:

$\pm 6\%$ , tracing to national standards (see table for other tolerances).

Application:

For ESD applications where recommended torque settings are important. Use in combination with a Wiha Torque ESD interchangeable blade.

Extra:

Delivered in practical plastic box, incl. factory calibration certificate.

Note:

Bit holders or blades are not included in delivery.

Further articles can be individualised and set at [mytorque.wiha.com](http://mytorque.wiha.com) or on request.

Order-No.	Nm	±%	○	↔	↓	⬮
36851	0.04-0.46*	10%	4	127	23	1
26865	0.1-0.6	10%	4	127	23	1
36852	0.1-0.6	6%	4	127	23	1
26629	0.4-1.0	6%	4	127	23	1
26866	0.8-2.0	6%	4	131	30	1
30495	1.0-5.0	6%	4	138	36	1

\* Precision in range of 0.1-0.46 Nm

## Wiha TorqueVario®-S ESD with integrated scale.

Specially designed for applications on electrostatic sensitive components and devices that may be damaged by electrostatic fields or discharges. The dissipative handle and blade coating, with a surface resistance of  $10^6 - 10^9$  Ohms, controls electrostatic energy discharge.

Four models cover torque ranges from 0.04 Nm up to 5.0 Nm.



## Wiha Torque ESD torque range.

- Dissipative handle designed to discharge uniformly, surface resistance  $10^6 - 10^9$  ohms

- Meets ESD standard IEC 61340-5-1

- Ergonomic SoftFinish® multi-component handle guarantees comfortable fastening and optimal handling

- Ergonomic handle sizes that are proportional to the torque ranges

- Each tool is individually tested and marked with an identification number

- Clearly audible and perceptible click signal when torque is reached

- Fulfills all accuracy requirements as defined by EN ISO 6789, BS EN 26789 and ASME B 107.14M

**Safety Notice:**

Wiha ESD screwdrivers are noninsulated, therefore not suitable for working on live parts.

**Torque ESD interchangeable blades.****2889 Torque ESD slotted interchangeable blade.**

For Wiha ESD torque screwdrivers.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.

Wiha ChromTop® finish on tip for a perfect fit every time.

Moulded with static dissipative, black plastic material.

Surface resistance  $10^6 - 10^9$  ohms.

Standards: IEC 61340-5-1, DIN ISO 2380.

Application: For ESD applications where recommended torque settings are important.

Order-No.	⌀	⌀	⌀	↔	↔	max. Nm	
26869	0.25	1.5	4	175	42	0.15	10
26870	0.4	2.0	4	175	42	0.4	10
26871	0.5	3.0	4	175	42	0.6	10
26872	0.6	3.5	4	175	42	1.1	10
26873	0.8	4.0	4	175	42	2.5	10

**2889 Torque ESD Phillips interchangeable blade.**

For Wiha ESD torque screwdrivers.

Blade: IEC 61340-5-1, DIN ISO 8764.

Order-No.	⊕	⌀	↔	↔	max. Nm	
26877	PH000	4	175	42	0.4	10
26876	PH00	4	175	42	0.4	10
26875	PH0	4	175	42	0.9	10
26878	PH1	4	175	42	3.8	10

**2889 Torque ESD Pozidriv interchangeable blade.**

For Wiha ESD torque screwdrivers.

Blade: IEC 61340-5-1, DIN ISO 8764.

Order-No.	⊕	⌀	↔	↔	max. Nm	
26879	PZ0	4	175	42	0.9	10
26880	PZ1	4	175	42	3.8	10

**2889 Torque ESD TORX® interchangeable blade.**

For Wiha ESD torque screwdrivers.

Blade: IEC 61340-5-1.

Application: Very slim blade diameter for hard-to-reach screws.

Order-No.	⊕	⌀	↔	↔	max. Nm	
26881	T5	4	175	42	0.4	10
26882	T6	4	175	42	0.6	10
26886	T7	4	175	42	0.9	10
26883	T8	4	175	42	1.3	10
26884	T9	4	175	42	2.5	10
26885	T10	4	175	42	3.8	10

**ESD bit holder and Torque Setter. Set.****2889 Torque ESD bit universal holder.**

For Wiha ESD torque screwdrivers.

Suitable for C 6.3 and E 6.3 (1/4") bits.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.

Surface resistance  $10^6 - 10^9$  ohms.

Sleeve: Made of stainless steel, moulded with dissipative, black plastic material.

Application: For ESD applications where recommended torque settings are important.

Order-No.	⌀	⌀	↔	↔	
27711	1/4	4	162	11	10

**288-900 Torque-Setter ESD.**

Setting tool for variable Torque ESD screwdrivers.

Included in every torque ESD screwdriver delivery.

Blade: Octagonal blade, through hardened, zinc-plated.

Handle: Made of static dissipative plastic material.

Standards: IEC 61340-5-1.

Supplement: Included in every torque screwdriver delivery.

Order-No.	↔	↔	
27279	80	150	1

**2882 S10**

TorqueVario®-S ESD torque screwdriver set, 13 pcs.

Torque value can be set via window scale.

With universal bit holder and 10 straight-blade/Phillips/Poszdriv/TORX® Standard bits.

Handle: Model 0.8-2.0 Nm.

Torque infinitely adjustable with Torque-Setter setting tool (also supplied). Ergonomic multi-component handle, made of ESD-safe dissipative material.

Standards: IEC 61340-5-1.

EN ISO 6798, BS EN 26789, ASME B107.14M.

Accuracy:  $\pm 6\%$ , traceable to national standards.

Application: For ESD applications where recommended torque settings are important.

Order-No.	Series	
27687	2882 S10	1
2882	TorqueVario®-S ESD, model 0.8-2.0 Nm	
2889	Torque ESD bit universal holder	
288-900	Torque-Setter ESD	
⌀	7010 Z	4.5x25 5.5x25
⊕	7011 Z	PH0x25 PH1x25
⊕	7012 Z	PZ0x25 PZ1x25
⊕	7015 Z	T7x25 T8x25 T9x25 T10x25

with scale